



Lubricants

Contents

| Contents | Pages | | | | | | |
|--|---------------|-------------|------------------------|---------|-----------------------|---------|-------------|
| | Rolls-Royce | | | Bentley | | | |
| | Silver Spirit | Silver Spur | Corniche / Corniche II | Eight | Mulsanne / Mulsanne S | Turbo R | Continental |
| Contents and issue record sheet | D1 | D1 | D1 | D1 | D1 | D1 | D1 |
| <i>Countries other than Canada and the USA</i> | D2 | D2 | D2 | D2 | D2 | D3 | D2 |
| <i>Canada and the USA</i> | D4 | D4 | D4 | D4 | D4 | D5 | D4 |



Issue record sheet

The dates quoted below refer to the issue date of individual pages within this chapter.

| Sections | D1 | D2 | D3 | D4 | D5 | | | | | | |
|----------|------|------|------|------|------|--|--|--|--|--|--|
| Page No. | | | | | | | | | | | |
| 1 | 5/88 | 5/88 | 5/88 | 5/88 | 5/88 | | | | | | |
| 2 | | 5/88 | 5/88 | 5/88 | 5/88 | | | | | | |
| 3 | 5/88 | | | | | | | | | | |
| 4 | | | | | | | | | | | |
| 5 | | | | | | | | | | | |
| 6 | | | | | | | | | | | |
| 7 | | | | | | | | | | | |
| 8 | | | | | | | | | | | |
| 9 | | | | | | | | | | | |
| 10 | | | | | | | | | | | |
| 11 | | | | | | | | | | | |
| 12 | | | | | | | | | | | |
| 13 | | | | | | | | | | | |
| 14 | | | | | | | | | | | |
| 15 | | | | | | | | | | | |
| 16 | | | | | | | | | | | |
| 17 | | | | | | | | | | | |
| 18 | | | | | | | | | | | |
| 19 | | | | | | | | | | | |
| 20 | | | | | | | | | | | |
| 21 | | | | | | | | | | | |
| 22 | | | | | | | | | | | |
| 23 | | | | | | | | | | | |
| 24 | | | | | | | | | | | |

| Sections | | | | | | | | | | | |
|----------|--|--|--|--|--|--|--|--|--|--|--|
| Page No. | | | | | | | | | | | |
| 1 | | | | | | | | | | | |
| 2 | | | | | | | | | | | |
| 3 | | | | | | | | | | | |
| 4 | | | | | | | | | | | |
| 5 | | | | | | | | | | | |
| 6 | | | | | | | | | | | |
| 7 | | | | | | | | | | | |
| 8 | | | | | | | | | | | |
| 9 | | | | | | | | | | | |
| 10 | | | | | | | | | | | |
| 11 | | | | | | | | | | | |
| 12 | | | | | | | | | | | |
| 13 | | | | | | | | | | | |
| 14 | | | | | | | | | | | |
| 15 | | | | | | | | | | | |
| 16 | | | | | | | | | | | |
| 17 | | | | | | | | | | | |
| 18 | | | | | | | | | | | |
| 19 | | | | | | | | | | | |
| 20 | | | | | | | | | | | |
| 21 | | | | | | | | | | | |
| 22 | | | | | | | | | | | |
| 23 | | | | | | | | | | | |
| 24 | | | | | | | | | | | |



Lubricants

All cars except Bentley Turbo R

† Engine, Hand oiling points

BP

BP Super Viscostatic
BP Visco 2000
BP Visco Route
BP Visco Coranda
BP Pilote 2500
BP Pilote 3000
BP Strato

Castrol

Castrol GTX
Castrol GTX2 (Turbo Tested)
Castrol Syntron
Castrol Syntron-X 5W/50
Castrol Formula RS

Duckhams

Duckhams Hypergrade
Duckhams 'QXR'

Esso

UNIFLO
Esso SUPERLUBE +
Esso Super Oil

Mobil

Mobil Super
Mobil 1 Rally Formula

Shell

Shell Super Motor Oil 20W/50
Shell Super Motor Oil 15W/50
Shell Super Motor Oil 15W/40
Shell Super Motor Oil 10W/40
Shell Super II

Texaco

Havoline 15W/40

† Recommended engine oil grades for cars operating in low temperatures.

For constant operation in ambient temperatures of between 0°C and -23°C (32°F and -10°F) use a 10W/30 grade oil.

For constant operation in ambient temperatures below -23°C (-10°F) use a 5W/20 grade oil alternatively, use Castrol Syntron-X 5W/50 oil or Mobil 1 Rally Formula (5W/50) oil.

Torque converter transmission, Steering pump

BP

BP Autran DX II

Castrol

Castrol TQ Dexron® II
Castrol Transmax M
Castrol Transmax S

Duckhams

Duckhams D-Matic ATF (Dexron II)

Esso

Esso ATF Dexron II

Gulf

Gulf Automatic Transmission Fluid Dexron II

Mobil

Mobil ATF 220 (Dexron)

Shell

Shell Automatic Transmission Fluid Dexron II

Texaco

Texamatic Fluid 9226 Dexron II

Also approved any other Dexron II Transmission Fluid.

Final drive unit, Rack and pinion steering unit

BP

BP Gear Oil 90 EP
BP Multigear FE 80W/90
BP Multigear FE 85W/140

Castrol

Castrol Hypoy EP 90
Castrol Hypoy B EP 90
Castrol EP 90
Castrol EPX 90
Castrol EPX 85W/140
Castrol EPX 80W/90

Duckhams

Duckhams Hypoid 90S

Esso

Esso Gear Oil GX 85W/90
Esso Gear Oil GX 80W

Gulf

Gulf Multi Purpose Gear Lubricant 80W/90

Mobil

Mobilube HD 90

Shell

Shell Spirax 90 EP



Front and rear hubs

BP

BP Energrease L2

Castrol

Castrol LM Grease

Duckhams

Duckhams LB 10 Grease

Esso

Esso Multi-purpose Grease

Gulf

Gulf Crown Grease No. 2 EP

Mobil

Mobilgrease MP

Shell

† Shell Retinax A

† First preference

**Rear drive-shaft constant velocity joints,
Levelling valve operating rod ball joints,
Parking brake linkage clevis and fulcrum pins**

Rocol

Rocol MTS 1000 Grease

Parking brake inner cable

Midlands Silicones

Midlands Silicones MS 44 Grease

Refrigeration compressor

Suniso

Suniso No. 5 GS Oil



**Hydraulic braking and levelling
systems**

Castrol

Castrol Hydraulic System Mineral Oil

Power operated hood reservoir

BP

BP Energol HLP 22

Castrol

Castrol Hyspin VG 22

Castrol Hyspin AWS 22

Esso

Esso Nuto H22

Gulf

Gulf Hydrasil 22

Mobil

Mobil DTE 11

Mobil DTE 12

Mobil DTE 13

Shell

Shell Tellus Oil 22

Alloy wheel trim locks

BP

Keenomax L3



Lubricants

Bentley Turbo R

† Engine, Hand oiling points

BP

BP Super Viscostatic
BP Visco 2000

Castrol

Castrol GTX
Castrol GTX 2 (Turbo Tested)
Castrol Syntron
Castrol Syntron-X 5W/50
Castrol Formula RS

Duckhams

Duckhams Hypergrade
Duckhams 'QXR'

Esso

Esso SUPERLUBE +
Esso Super Oil 15W/40

Mobil

Mobil Super
Mobil 1 Rally Formula

Shell

Shell Super Motor Oil 20W/50
Shell Super Motor Oil 15W/50
Shell Super Motor Oil 15W/40
Shell Super II

Texaco

Havoline 15W/40

† Recommended engine oil grades for cars operating in low temperatures.

For constant operation in ambient temperatures of between 0°C and -23°C (32°F and -10°F) use a 10W/40 grade oil.

For constant operation in ambient temperatures below -23°C (-10°F) use a 5W/20 grade oil or alternatively, use Castrol Syntron-X 5W/50 oil or Mobil 1 Rally Formula (5W/50) oil.

Torque converter transmission, Steering pump

BP

BP Aufran DX II

Castrol

Castrol TQ Dexron® II
Castrol Transmax M
Castrol Transmax S

Duckhams

Duckhams D-Matic ATF (Dexron II)

Esso

Esso ATF Dexron II

Gulf

Gulf Automatic Transmission Fluid Dexron II

Mobil

Mobil ATF 220 (Dexron)

Shell

Shell Automatic Transmission Fluid Dexron II

Texaco

Texamatic Fluid 9226 Dexron II

Also approved any other Dexron II Transmission Fluid.

Final drive unit, Rack and pinion steering unit

BP

BP Gear Oil 90 EP
BP Multigear FE 80W/90
BP Multigear FE 85W/140

Castrol

Castrol Hypoy EP 90
Castrol Hypoy B EP 90
Castrol EP 90
Castrol EPX 90
Castrol EPX 85W/140
Castrol EPX 80W/90

Duckhams

Duckhams Hypoid 90S

Esso

Esso Gear Oil GX 85W/90
Esso Gear Oil GX 80W

Gulf

Gulf Multi Purpose Gear Lubricant 80W/90

Mobil

Mobilube HD 90

Shell

Shell Spirax 90 EP

Front and rear hubs, Propeller shaft universal joints

BP

BP Energrease L2



Castrol
Castrol LM Grease

Duckhams
Duckhams LB 10 Grease

Esso
Esso Multi-purpose Grease

Gulf
Gulf Crown Grease No. 2 EP

Mobil
Mobilgrease MP

Shell
† Shell Retinax A

† First preference

**Rear drive-shaft constant velocity joints,
Levelling valve operating rod ball joints,
Parking brake linkage clevis and fulcrum pins**

Rocol
Rocol MTS 1000 Grease

Parking brake inner cable

Midlands Silicones
Midlands Silicones MS 44 Grease

Refrigeration compressor

Suniso
Suniso No. 5 GS Oil



**Hydraulic braking and levelling
systems**

Castrol
Castrol Hydraulic System Mineral Oil

Alloy wheel trim locks

BP
Keenomax L3



Lubricants

All cars except Bentley Turbo R

† Engine, Hand oiling points

BP

BP Super Viscostatic
BP Visco 2000

Castrol

Castrol GTX (USA)
Castrol XLR (Canada)
Castrol Syntrol-X 5W/50

Duckhams

Duckhams Hypergrade
Duckhams 'QXR'

Exxon/Esso

Superflo Supreme Performance (USA)
Protec Ultra (Canada)
UNIFLO

Mobil

Mobil Super
Mobil 1 Rally Formula

Shell

Fire and Ice (USA)
Super Plus (Canada)

Texaco

Havoline 15W/40

† Recommended engine oil grades for cars operating in low temperatures.

For constant operation in ambient temperatures of between 0°C and -23°C (32°F and -10°F) use a 10W/30 grade oil.

For constant operation in ambient temperatures below -23°C (-10°F) use a 5W/20 grade oil alternatively, use Castrol Syntrol-X 5W/50 or Mobil 1 Rally Formula (5W/50) oil.

Torque converter transmission, Steering pump

BP

BP Autran Universal

Castrol

Castrol TQ Dexron[®] II
Castrol Transmax M
Castrol Transmax S

Duckhams

Duckhams D-Matic ATF (Dexron II)

Exxon/Esso

Esso ATF Dexron II

Gulf

Gulf Automatic Transmission Fluid Dexron II

Mobil

Mobil ATF 220 (Dexron)

Shell

Shell Automatic Transmission Fluid Dexron II

Texaco

Texamatic Fluid 9226 Dexron II

Also approved any other Dexron II Transmission Fluid

Final drive unit, Rack and pinion steering unit

BP

BP GEAREP 80W/90
BP GEAREP 80W/140
BP GEAREP 85W/140

Castrol

Castrol EP 90
Castrol EPX 90
Castrol EPX 85W/140
Castrol EPX 80W/90

Duckhams

Duckhams Hypoid Gear Oil 80W/90

Exxon/Esso

Esso Gear Oil GX 85W/140
Esso Gear Oil GX 85W/90
Esso Gear Oil GX 80W/90
Esso Gear Oil GX 80W

Gulf

Gulf Multi Purpose Gear Lubricant 80W/90

Mobil

Mobilube HD 90

Shell

Shell Spirax 90 EP

Front and rear hubs

BP

BP Energrease L2

**Castrol**

Castrol MP Grease
Castrol LM Grease
Castrol Universal Wheel Bearing Grease (Canada)

Duckhams

Duckhams LB 10 Grease

Exxon/Esso

Ronex MP
Esso Unitol

Gulf

Gulf Crown Grease No. 2 EP

Mobil

Mobilgrease MP

Shell

Shell Darina AX

**Rear drive-shaft constant velocity joints,
Levelling valve operating rod ball joints,
Parking brake linkage clevis and fulcrum pins**

Rocol

Rocol MTS 1000 Grease

Parking brake inner cable**Midlands Silicones**

Midlands Silicones MS 44 Grease

Refrigeration compressor**Suniso**

Suniso No. 5 GS Oil



**Hydraulic braking and levelling
systems**

Castrol

Castrol Hydraulic System Mineral Oil

Power operated hood reservoir**BP**

BP Energol HLP 22

Castrol

Castrol Hyspin AWS 22

Exxon/Esso

Esso Nuto H22

Gulf

Gulf Harmony 22 AW

Mobil

Mobil DTE 11
Mobil DTE 12
Mobil DTE 13

Shell

Shell Tellus Oil 22
Shell Tellus Oil 23

Alloy wheel trim locks**BP**

Keenomax L3



Lubricants

Bentley Turbo R

† Engine, Hand oiling points

BP

BP Super Viscostatic 10W/40
BP Visco 2000

Castrol

Castrol GTX (USA)
Castrol XLR (Canada)
Castrol Syntron-X 5W/50

Duckhams

Duckhams Hypergrade
Duckhams 'QXR'

Exxon/Esso

Superflo Supreme Performance (USA)
Protec Ultra (Canada)

Mobil

Mobil Super
Mobil 1 Rally Formula

Shell

Fire and Ice (USA)
Super Plus (Canada)

Texaco

Havoline 15W/40

† Recommended engine oil grades for cars operating in low temperatures.

For constant operation in ambient temperatures of between 0°C and -23°C (32°F and -10°F) use a 10W/40 grade oil.

For constant operation in ambient temperatures below -23°C (-10°F) use a 5W/20 grade oil alternatively, use Castrol Syntron-X 5W/50 or Mobil 1 Rally Formula (5W/50) oil.

Torque converter transmission, Steering pump

BP

BP Autran Universal

Castrol

Castrol TQ Dexron® II
Castrol Transmax M
Castrol Transmax S

Duckhams

Duckhams D-Matic ATF (Dexron II)

Exxon/Esso

Esso ATF Dexron II

Gulf

Gulf Automatic Transmission Fluid Dexron II

Mobil

Mobil ATF 220 (Dexron)

Shell

Shell Automatic Transmission Fluid Dexron II

Texaco

Texamatic Fluid 9226 Dexron II

Also approved any other Dexron II Transmission Fluid.

Final drive unit, Rack and pinion steering unit

BP

BP GEAREP 80W/90
BP GEAREP 80W/140
BP GEAREP 85W/140

Castrol

Castrol EP 90
Castrol EPX 90
Castrol EPX 85W/140
Castrol EPX 80W/90

Duckhams

Duckhams Hypoid Gear Oil 80W/90

Exxon/Esso

Esso Gear Oil GX 85W/140
Esso Gear Oil GX 85W/90
Esso Gear Oil GX 80W/90
Esso Gear Oil GX 80W

Gulf

Gulf Multi Purpose Gear Lubricant 80W/90

Mobil

Mobilube HD 90

Shell

Shell Spirax 90 EP

Front and rear hubs, Propeller shaft universal joints

BP

BP Energrease L2

Castrol

Castrol MP Grease
Castrol LM Grease
Castrol Universal Wheel Bearing Grease (Canada)



Duckhams

Duckhams LB 10 Grease

Exxon/Esso

Ronex MP

Esso Unitol

Gulf

Gulf Crown Grease No. 2 EP

Mobil

Mobilgrease MP

Shell

Shell Darina AX

**Rear drive-shaft constant velocity joints,
Levelling valve operating rod ball joints,
Parking brake linkage clevis and fulcrum pins**

Rocol

Rocol MTS 1000 Grease

Parking brake inner cable

Midlands Silicones

Midlands Silicones MS 44 Grease

Refrigeration compressor

Suniso

Suniso No. 5 GS Oil



**Hydraulic braking and levelling
systems**

Castrol

Castrol Hydraulic System Mineral Oil

Alloy wheel trim locks

BP

Keenomax L3